

(12) United States Patent Smith et al.

(10) **Patent No.:**

US 7,957,768 B2

Jun. 7, 2011

(45) Date of Patent:

(75) Inventors: Elizabeth Smith, San Diego, CA (US); Mary Lauricella, Schiller Park, IL (US)

Assignee: AT&T Intellectual Property I, L.P.,

Atlanta, GA (US)

Subject to any disclaimer, the term of this (*) Notice:

patent is extended or adjusted under 35

U.S.C. 154(b) by 860 days.

Appl. No.: 11/846,341

Aug. 28, 2007 (22)Filed:

(65)**Prior Publication Data**

> US 2009/0061942 A1 Mar. 5, 2009

(51) Int. Cl. H04M 1/00 (2006.01)

(52)**U.S. Cl.** **455/566**; 455/556.1; 455/575.4;

345/168; 361/683

455/550.1, 575.1, 575.4, 556.1; 345/168; 296/287; 361/683

See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

2/1993 Paaianen et al. 5.189.632 A 4/2000 Makela et al. 6,047,196 A 6,233,467 B1 5/2001 Rydbeck

6,415,138	B2	7/2002	Sirola et al.
6,587,096	B2 *	7/2003	Bullister 345/168
6,983,170	B2	1/2006	Stulberger
7,489,503	B2 *	2/2009	Maatta 361/679.27
2006/0159443	A1*	7/2006	Cho et al 396/287

OTHER PUBLICATIONS

Greatcall, Inc., "Easy Emergency Cell Phones",2006-2007, Jitterburg Phones, 1 page article, www.jitterbug.com, web site last visited Aug. 28, 2007.

* cited by examiner

Primary Examiner — Danh C Le (74) Attorney, Agent, or Firm — Moazzam & Associates, LLC

ABSTRACT (57)

A system that incorporates teachings of the present disclosure may include, for example, a wireless communication device including a housing assembly formed from a first section that is rotatably coupled about an axis to a second section such that the first and second sections are movable between a closed position in which a first side of the first section is aligned with and in close proximity to a first side of the second section. The wireless communication device can also include a first display screen positioned in the first section and a second display screen positioned in the second section. The first and second display screens can be configured to display images. The wireless communication device can also include a keypad including keys on the first and second sections, thereby creating a foldable keypad rotatable about the axis between the first and second sections. Additional embodiments are disclosed.

14 Claims, 5 Drawing Sheets

